GENERAL SPECIFICATION FOR CIVIL ENGINEERING WORKS

1992 Edition

CORRIGENDUM No. 1/98 (June)

VOLUME 1

SECTION 5	DRAINAGE WORKS
(a) Page 137, Clause 5.86, 3rd line	Replace compacting by compaction
(b) Page 137, Clause 5.87, Marginal heading	Replace compacting by compaction
(c) Page 137, Clause 5.87, 1st line	Replace compacting by compaction
(d) Page 137, Clause 5.87(a), 1st line	Replace compacting by compaction
(e) Page 137, Clause 5.87(b), 1st line	Replace compacting by compaction
(f) Page 144, Appendix 5.2, Title, 1st line	Replace COMPACTING by COMPACTION
(g) Page 144, Appendix 5.2, Clause 5.2.1, 1st line	Replace compacting by compaction
(h) Page 144, Appendix 5.2, Clause 5.2.4, 1st line	Replace compacting factor by compaction fraction
(i) Page 144, Appendix 5.2, Clause 5.2.4, 3rd line	Replace Compacting factor by Compaction fraction

(j) Page 145, Appendix 5.2, Clause 5.2.5(b) Replace compacting factor by compaction fraction

VOLUME 2

SECTION 14

FORMWORK AND FINISHES TO CONCRETE

(a) Page 150, Clause 14.35(1), 5th line Add not exceeding the OPC replacement level as specified in Clause 16.14. after or both OPC and PFA

SECTION 16

CONCRETE AND JOINTS IN CONCRETE

(a) Page 176, Clause 16.14 (4) Replace the clause by the following:

When PFA is incorporated in the concrete as a separate material, its proportion shall not exceed 35% of the total cementitious content for normal concrete. If other conditions apply, particulars of proposed changes to the proportion of PFA shall be submitted to the Engineer for approval.

Standards Unit Civil Engineering Department June 1998