


NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. ALL WELDS SHALL BE CHIPPED, GROUND SMOOTH, BRUSHED TO REMOVE SLAG AND PROTECTED BY TWO COATS OF ZINC RICH PAINT TO BS4652.
3. ALL STEELWORK SHALL BE HOT DIP GALVANIZED.
4. ALL STEEL POSTS AND TUBES SHALL COMPLY WITH BS EN 10255 (MEDIUM AND HEAVY SERIES TUBES).
5. ALL STEEL ANGLES SHALL COMPLY WITH BS EN 10025 AND BS EN 10056.
6. WHERE STAIRCASE SITS ON GOOD QUALITY ROCK, BOLTS AND BASE PLATE CAN BE USED AS APPROPRIATE. SEE DETAILS OF BASE PLATE AS AN ALTERNATIVE.
7. ALL EXPOSED STEELWORK SURFACES SHALL BE TREATED AND PAINTED IN ACCORDANCE WITH THE GENERAL SPECIFICATION AND PARTICULAR SPECIFICATION OR AS SPECIFIED BY THE ENGINEER.

ELEVATION
SCALE 1:25

A	BIM OBJECT REVISION.	Original Signed	12.2025
-	FORMER DRG. NO. C2102J.	Original Signed	03.2015
REF.	REVISION	SIGNATURE	DATE

**STEEL STAIRCASE FOR
SLOPE STEEPER THAN 40°
(SHEET 1 OF 2)**

 CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT	
SCALE AS SHOWN	DRAWING NO.
DATE JAN 1991	C2102 /1A