


DETAILS OF STEEL ANGLE BASE

NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. ALL WELDS SHALL BE CHIPPED AND GROUND SMOOTH AND BRUSHED TO REMOVE SLAG AND PROTECTED BY TWO COATS OF ZINC RICH PAINT TO BS4652.
3. ALL STEELWORK SHALL BE HOT DIP GALVANIZED.
4. ALL STEEL POSTS AND TUBES SHALL COMPLY WITH BS EN 10255 (MEDIUM AND HEAVY SERIES TUBES)
5. ALL STEEL ANGLES SHALL COMPLY WITH BS EN 10025 AND BS EN 10056.
6. CONCRETE TO BE PAINTED AS SPECIFIED.
7. ALL EXPOSED STEELWORK SURFACES SHALL BE TREATED AND PAINTED IN ACCORDANCE WITH THE GENERAL SPECIFICATION AND PARTICULAR SPECIFICATION OR AS SPECIFIED BY THE ENGINEER.
8. ALL STAINLESS STEEL ANCHOR BOLTS AND WASHERS SHALL HAVE A DECLARATION OF PERFORMANCE FOR THE CONSTRUCTION PRODUCT COVERED BY A EUROPEAN TECHNICAL ASSESSMENT REPORT ETAG 001 OR APPROVED EQUIVALENT.

A	BIM OBJECT REVISION.	Original Signed	12.2025
-	FORMER DRG. NO. C2103K	Original Signed	08.2024
REF.	REVISION	SIGNATURE	DATE

HANDRAILING TO MAINTENANCE STAIRWAY ON SLOPE (SHEET 2 OF 2)

 CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT		DRAWING NO.	
		C2103 /2A	
SCALE	1 : 5	DATE	JAN 1991