



NOTES :

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. WHERE THE CONCRETE FOOTING IS LOCATED IN BLOCK PAVED FOOTPATH, THE FOOTING SHOULD BE LOWERED TO ALLOW FOR THE PAVING BLOCKS AND THE SAND COURSE.
3. ALL STEELWORK EXCEPT CORRUGATED STEEL SHEETING SHALL BE GRADE S275 STEEL TO BS EN 10025 AND SHALL BE PAINTED WITH SYSTEM A PAINT STATED IN APPENDIX 18.2.2 OF GS 2020.
4. CORRUGATED STEEL SHEETING SHALL HAVE SECTION MODULUS NOT LESS THAN 2000mm³ /m. THE SHEETING SHALL BE TO BS 3083:1988 8/3 Z350.
5. ALTERNATIVE CONSTRUCTION DETAILS (INCLUDING FOUNDATION DETAILS) FOR THE SITE HOARDING, WHICH MUST BE CAPABLE OF WITHSTANDING A WIND PRESSURE OF 1.2 kPa, SHALL BE SUBMITTED TO THE ENGINEER FOR AGREEMENT.
6. ALL CONCRETE SHALL BE GRADE 20/20. RECYCLED AGGREGATES SHALL BE USED WHERE AVAILABLE.
7. ALL LETTERING SHALL BE IN BLACK EXCEPT OTHERWISE STATED.
8. REFER TO LATEST VERSION OF DRG. No. C1004/2 FOR SECTION A-A.
9. REFER TO LATEST VERSION OF DRG. No. C1001 FOR DETAILS OF THE DEPARTMENTAL LOGO.
10. THE TELEPHONE NO. FOR ANY ENQUIRIES OR COMPLAINTS SHALL BE GIVEN BY THE ENGINEER.
11. REFER TO LATEST VERSION OF DRG. No. C1012 FOR VMV SIGN DETAILS. THE CHINESE AND ENGLISH VERSIONS OF VMV SIGN SHALL BE DISPLAYED AT ALTERNATE POSITIONS OF HOARDING.
12. REFER TO LATEST VERSION OF DRG. No. C1021 FOR CI LOGO DETAILS.
13. FONT TYPE OF "土木工程拓展署" SHALL BE MHEIHK BOLD.
14. FONT TYPE OF "CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT" SHALL BE MYRIAD ROMAN.

REF.	REVISION	SIGNATURE	DATE
Q	NOTE 3 AMENDED	Original Signed	01.2022
P	NOTE 3 AMENDED	Original Signed	09.2018
O	NOTES 3, 4 & TITLE AMENDED	Original Signed	03.2015
N	FRONT ELEVATION, FRONT ELEVATION OF DEPARTMENTAL LOGO PANEL AND NOTES REVISED	Original Signed	08.2011
M	FRONT ELEVATION AND NOTES REVISED	Original Signed	07.2011

HOARDING TYPE I
(SHEET 1 OF 3)

CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

SCALE AS SHOWN	DRAWING NO. C1004/1Q
DATE OCT 1991	

卓越工程 建設香港 We Engineer Hong Kong's Development