



M10 GMS SCREW & NUT

FRONT ELEVATION OF DEPARTMENTAL LOGO PANEL

- 2. WHERE THE CONCRETE FOOTING IS LOCATED IN BLOCK PAVED FOOTPATH, THE FOOTING SHOULD BE LOWERED TO ALLOW FOR THE PAVING BLOCKS AND THE SAND COURSE.
- 3. ALL STEELWORK EXCEPT CORRUGATED STEEL SHEETING SHALL BE GRADE S275 STEEL TO BS EN 10025 AND SHALL BE PAINTED WITH SYSTEM A PAINT STATED IN APPENDIX 18.2.2 OF GS 2020.
- 4. CORRUGATED STEEL SHEETING SHALL HAVE SECTION MODULUS NOT LESS THAN 2000mm³/m. THE SHEETING SHALL BE TO BS 3083:1988 8/3 Z350.
- 5. ALTERNATIVE CONSTRUCTION DETAILS (INCLUDING FOUNDATION DETAILS) FOR THE SITE HOARDING, WHICH MUST BE CAPABLE OF WITHSTANDING A WIND PRESSURE OF 1.2 kPa, SHALL BE SUBMITTED TO THE ENGINEER FOR AGREEMENT.
- 6. ALL CONCRETE SHALL BE GRADE 20/20. RECYCLED AGGREGATES SHALL BE USED WHERE AVAILABLE.
- 7. ALL LETTERING SHALL BE IN BLACK EXCEPT OTHERWISE STATED.
- 8. REFER TO LATEST VERSION OF DRG. No. C1004/2 FOR SECTION A-A.
- 9. REFER TO LATEST VERSION OF DRG. No. C1001 FOR DETAILS OF THE DEPARTMENTAL LOGO.
- 10. THE TELEPHONE NO. FOR ANY ENQUIRIES OR COMPLAINTS SHALL BE GIVEN BY THE ENGINEER.
- 11. REFER TO LATEST VERSION OF DRG. No. C1012 FOR VMV SIGN DETAILS.
- 12. REFER TO LATEST VERSION OF DRG. No. C1021 FOR CILOGO DETAILS.
- 13. FONT TYPE OF "土木工程拓展署" SHALL BE MHEIHK BOLD.
- 14. FONT TYPE OF "CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT" SHALL BE MYRIAD ROMAN.

REF.	REVISION	SIGNATURE	DATE
N	FRONT ELEVATION, FRONT ELEVATION OF DEPARTMENTAL LOGO PANEL AND NOTES REVISED	Original Signed	08.2011
O	NOTES 3, 4 & TITLE AMENDED	Original Signed	03.2015
Р	NOTE 3 AMENDED	Original Signed	09.2018
Q	NOTE 3 AMENDED	Original Signed	01.2022
R	VMV SIGN AMENDED	Original Signed	06.2025

HOARDING TYPE I (SHEET 1 OF 3)



CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

SCALE AS SHOWN
DATE OCT 1991

C1004/1R