## NOTES:

- 1 ALL DIMENSIONS ARE IN MILLIMETRES
- PUBLICITY BOARDS SHALL BE MADE OF 3 mm THICK ALUMINIUM PLATE CONFORMING TO BS EN 485.
- 3. THE FACE OF THE BOARD SHALL BE CONSTRUCTED WITH CLASS REF 1 REFLECTIVE MATERIALS TO BS EN 12899-1.
- 4. DETAILS OF THE DEPARTMENTAL LOGO SHALL BE IN ACCORDANCE WITH DRG. NO. C1001.
- 5. DETAILS OF THE CARTOON FIGURE SHALL BE IN ACCORDANCE WITH DRG. NO. C1017.
- 6. THE SIZE OF THE TELEPHONE FIGURE SHALL BE 33 x 33 mm.
- 7. SIZE OF LETTERING:

	ENGLISH			CHINESE				NUMBER	
HEIGHT (mm)	18	12	8	54	28	21	12	30	18
WIDTH (mm)	14	10	6	54	28	21	12	24	14

- 8. THE ORIGINAL COMPLETION DATE SHALL BE APPROVED BY THE ENGINEER.
- 9. THE ANTICIPATED COMPLETION DATE SHALL INDICATE THE BEST ESTIMATED DATE OF RE-OPENING THE ROAD (WHICH IS NOT NECESSARY THE CONTRACTUAL COMPLETION DATE OR EXCAVATION PERMIT EXPIRY DATE ) AND BE APPROVED BY THE ENGINEER.
- 10. THE ANTICIPATED COMPLETION DATE OF THIS SECTION SHALL INDICATE THE BEST ESTIMATED DATE OF RE-OPENING THIS SECTION OF ROAD (WHICH IS NOT NECESSARY THE CONTRACTUAL COMPLETION DATE OR EXCAVATION PERMIT EXPIRY DATE ) AND BE APPROVED BY THE ENGINEER.
- 11. THE ORIGINAL COMPLETION DATE OF THIS SECTION SHALL BE APPROVED BY THE ENGINEER.
- 12. THE TELEPHONE NO. FOR ANY ENQUIRIES OR COMPLAINTS SHALL BE GIVEN BY THE ENGINEER.
- 13. THE INFORMATION ON THIS PUBLICITY BOARD SHALL BE PRINTED IN CHINESE AND ENGLISH AND SHALL BE CLEAR AND LEGIBLE. FREE-HAND WRITING IS NOT PERMITTED.
- 14. FOR WORKS SITES LESS THAN 50 METRES IN LENGTH, ONE NOTICE BOARD SHALL BE PROVIDED.
  FOR WORKS SITES LONGER THAN 50 METRES IN LENGTH, NOTICE BOARDS SHALL BE PROVIDED AT
  THE ENDS OF THE SITE AND ALONG THE SITE AT A MAXIMUM SPACING OF 50 METRES.
- 15. DESCRIPTION OF WORKS SHALL BE APPROVED BY THE ENGINEER.
- 16. COLOUR OF PAINTING TO BS 5252F:
  - (a) LETTERS, CHARACTERS & LINES: BLACK
  - (b) OTHER: YELLOW

CODE 00E53 CODE 08E51

- 17. BOLTS SHALL BE M6 DOME HEAD HOT-DIP GALVANISED TO BS EN ISO 1461. OTHER SUITABLE BOLTS MAY BE USED AS APPROVED BY THE ENGINEER.
- 18. THE PUBLICITY BOARD SHALL BE MOUNTED ON A STABLE STRUCTURE (E.G. TEMPORARY BARRIER, HOARDING OR RAILING).
- 19. THE PUBLICITY BOARD SHALL BE CLEAN AND CLEAR FROM DAMAGE WITH MESSAGE CLEARLY LEGIBLE.
- 20. ALL EDGES OF A SIGN PLATE SHALL BE GROUND TO ENSURE THAT THEY ARE FREE FROM SHARP EDGES, BURRS, RAGGEDNESS AND TEARS.
- 21. NAME OF CONTRACTOR SHALL BE MARKED IN BOTH ENGLISH AND CHINESE ON THE BACK OF EACH SIGN.

REF.	REVISION	SIGNATURE	DATE
-	NEW ISSUE.	Original Signed	01.2010
Α	MINOR AMENDMENT	Original Signed	03.2015
В	NOTE 17 AMENDED	Original Signed	09.2018

SMALL PUBLICITY BOARD FOR PEDESTRIANS – TYPE 'A' AND TYPE 'B' (SHEET 3 OF 3 )

卓越工程 建設香港



CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

SCALE N. A. DRAWING NO. C1014/3B

We Engineer Hong Kong's Development