
DIMENSION TABLE



TYPICAL SECTION OF SOIL NAIL HEAD

1/2 L 1/2 L ₹ 2

30 MPa SPRAYED CONCRETE

150 x 150 x 20 Tk GMS PLATE. THE DIAMETER OF THE OPENING TO RECEIVE SOIL NAIL STEEL

BAR SHALL NOT BE LARGER THAN THE DIAMETER

SOIL NAIL HEAD

OF THE STEEL BAR BY 2 mm

VIEW NORMAL TO SOIL NAIL HEAD

TYPICAL DETAILS OF SOIL NAIL (SHEET 2 OF 8)

卓越工程 建設香港

NOTES:

(REFER TO DIMENSION TABLE)

REINFORCEMENT

THIN NUT (SEE NOTE 5)

- 1. ALL DIMENSIONS ARE IN MILLIMETRES.
- 2. THE SIZE OF SOIL NAIL HEAD SHALL BE SPECIFIED BY THE ENGINEER.
- 3. CONSTRUCTION OF SOIL NAIL HEAD SHALL BE REFERRED TO GENERAL SPECIFICATION FOR CIVIL ENGINEERING WORKS.
- 4. B DENOTES GRADE 500B RIBBED REINFORCEMENT.
- 5. FOR SOIL NAIL HEADS CONSTRUCTED BY 2-STAGE SPRAYED CONCRETE ACCORDING TO GENERAL SPECIFICATION FOR CIVIL ENGINEERING WORKS, THE THIN NUT SHALL BE OMITTED.

REF.	REVISION	SIGNATURE	DATE
-	NEW ISSUE.	Original Signed	10.2003
Е	DIMENSION TABLE ADDED. 10 DIA. HOLE ON GMS PLATE ADDED.	Original Signed	01.2005
F	NOTES AMENDED.	Original Signed	02.2008
G	BAR NOTATIONS AMENDED.	Original Signed	12.2014
н	DRAWING TITLE AND SUB-TITLE AMENDED.	Original Signed	03.2015
J	TITLE REVISED.	Original Signed	06.2015
K	NOTE 3 AMENDED AND NOTE 5 ADDED.	Original Signed	04.2016



CIVIL ENGINEERING AND **DEVELOPMENT DEPARTMENT**

SCALE DIAGRAMMATIC **DATE** OCT 2003

DRAWING NO. C2106 / 2K

We Engineer Hong Kong's Development