


NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETRES
- DETAILS OF BENCHING FOR PLACEMENT OF FILL ARE SHOWN ON STD. DRG. NO. C2301.
- 3. FINE GRANULAR FILTER SERVES AS FILTER FOR SOIL.
 COARSE GRANULAR FILTER SERVES AS FILTER FOR
 FINE GRANULAR FILTER. THE GRANULAR FILTERS SHALL BE
 DESIGNED BY THE CONTRACTOR IN ACCORDANCE WITH
 GEO PUBLICATION NO. 1/93.
- 4. DIMENSIONS OF TEMPORARY CUT TO BE SPECIFIED BY THE ENGINEER. SUPPORT TO THE TEMPORARY CUT SHALL BE DESIGNED BY THE CONTRACTOR.
- 5. SINGLE LAYER OF 500 mm THICK GRANULAR FILTER LAYER SHALL BE USED FOR ROCKFILL.



DETAIL 'Y'

	REF.	REVISION	SIGNATURE	DATE
	А	MINOR AMENDMENT.	Original Signed	3.94
	В	MINOR AMENDMENT.	Original Signed	1.96
	С	LAYOUT REVISED AND DETAIL 'X' ADDED.	Original Signed	6.99
	D	GENERAL REVISION.	Original Signed	12.2002
	Е	DETAIL 'Y' AMENDED.	Original Signed	01.2004
l	F	NAME OF DEPARTMENT AMENDED.	Original Signed	01.2005

FILTER BLANKET FOR FILL SLOPE AND FILLING DETAILS AT SLOPE CREST

興土木 利民生 齊拓展 創明天



CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

SCALE AS SHOWN DRAWING NO. C2302F

We bring the best engineering to life