



**NOTES :**

1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. ALL LEVELS REFER TO PRINCIPAL DATUM (PD) AND ARE IN MILLIMETRES.
3. THE ANCHORAGE LOCATION OF 65x12 TK STAINLESS STEEL FLAT SHALL AVOID THE MORTAR BETWEEN GRANITE FACING STONES.
4. ALL STAINLESS STEEL SHALL BE GRADE 1.4401.

REF.	REVISION	SIGNATURE	DATE
E	NOTES 4 ADDED	Original Signed	03.2015
D	CAT LADDER SEPARATED INTO 3 PARTS AND SUPPORTS AND THICKNESS OF CAT LADDER AMENDED.	Original Signed	03.2012
C	ENLARGED DETAIL - CAT LADDER SEPARATED INTO 2 PARTS	Original Signed	10.2004
B	NAME OF DEPARTMENT AMENDED.	Original Signed	09.2004
A	LEVELS REVISED TO PD, STAINLESS STEEL SECTIONS OF CAT LADDER REVISED AND MAXIMUM SPACING OF ANCHORAGE OF CATLADDER ADDED.	Original Signed	12.2002

**GRAVITY SEAWALL  
CAT LADDER TYPE III**



**CIVIL ENGINEERING AND  
DEVELOPMENT DEPARTMENT**

**SCALE AS SHOWN**

**DRAWING NO.**

**DATE JAN 1991**

**C3013E**